



Gammacolor s.r.l.
Via Zeuner, 5 20822 Seveso (MB) Italy
tel. +39 0362550550 fax +39 0362551915
email info@gammacolorsrl.com



Associazione Tessile e Salute
Azienda associata

p.IVA 00736390964 C.F. 02639210158 c.c.i.a. Milano n. 927455 Codice ISS azienda 00736390964

ANTIBASTONANTE PES

Agent universal anticrack marks agents suitable for every type of fabric and fiber.

Chemical nature: polyacrylamide

Appearance: turbid liquid

Ionic charge: nonionic

Solubility: soluble in cold or lukewarm water

Compatibility: totally

Resistance: resistant to acids, alkalis and hard water

Stability: 12 months under proper conditions

Application

Antibastonante PES is used both in winch dyeing and jet dyeing for every kind of fabric even delicate items in PES, PA or viscose and blends.

For its strong stability it is not required the application of a defoamer and has no retarding effect of acid, direct dyes, reactive and dispersed.

Method of application

It is diluted in cold or warm water, with a good agitation of the bath can also be added directly into the cycle.

The dosages are 1-3 g/L but we recommend the customer to vary the quantities according to the structure of the fabric.

Keywords: anti crack mark, anticrack

These notes are for information purposes only and does not imply any liability on the part of Gammacolor.

For information: e-mail info@gammacolorsrl.com