



Gammacolor s.r.l.
Via Zeuner, 5 20822 Seveso (MB) Italy
tel. +39 0362550550 fax +39 0362551915
email info@gammacolorsrl.com



Associazione Tessile e Salute
Azienda associata

p.IVA 00736390964 C.F. 02639210158 c.c.i.a. Milano n. 927455 Codice ISS azienda 00736390964

GAMMAPRET PE

Soluble synthetic resin specific for the sizing of Denim fabrics warp

Chemical character: polyester resin in aqueous solution

Ionic character: anionic

Incompatible substances: cationic substances and concentrated alkalis

Properties:

Gammaret PE eliminates dustiness in the operations of weaving. It also improves the yarn fluency at the loom as it's insensitive to heat and wet.

It is also used as a finishing for the preparation of fabric ribbons.

Doses of use: from 100 to 300 g / l depending on the desired hand.

Special warnings:

avoid mixing Gammaret PE with concentrated alkalis (irreversible precipitation occurs)

Keywords: size, sizing, polyester, abrasion, denim

The above data are the result of accurate studies and/or of the experience acquired; however, they are to be taken as an indication and in any case with no guarantee on our side as far as employment is concerned. The data contained in this data sheet are not to be regarded as technical specifications. For information, please contact: **e-mail address**

info@gammacolorsrl.com