



Gammacolor s.r.l.
Via Zeuner, 5 20822 Seveso (MB) Italy
tel. +39 0362550550 fax +39 0362551915
email info@gammacolorsrl.com



Associazione Tessile e Salute
Azienda associata

p.IVA 00736390964 C.F. 02639210158 c.c.i.a. Milano n. 927455 Codice ISS azienda 00736390964

GAMMAPRET PO

Product based on partially hydrolysed polyvinyl resins in aqueous solution.

Physical and chemical properties:

Appearance: Dense liquid

Color: White

pH: 5.0 - 7.0

Anionic Character

Solubility in water: Miscible as desired

Brookfield LVDV II viscosity at 25 ° C: 1800 - 2200 cPs, Spindle 3, Rpm 30

Purity / Active product: 9 – 11%

Application:

GAMMAPRET PO for its adhesive concentration and viscosity is a product designed for printing on a rotary press.

With appropriate dilutions in water, GAMMAPRET PO allows the preparation of the fabric on the printing plane in the most precise way, to avoid any form of replication or duplication of the drawings.

GAMMAPRET PO must be employed along with an anti-foam agent, due to the movement of cylinders.

It is advisable to store the product in original sealed containers, between 5 ° C and 35 ° C, protected from frost and away from sources of heat.

Keywords: rotary printing, rotary

The above data are the result of accurate studies and/or of the experience acquired; however, they are to be taken as an indication and in any case with no guarantee on our side as far as employment is concerned. The data contained in this data sheet are not to be regarded as technical specifications. For information, please contact: **e-mail address**

info@gammacolorsrl.com