



Gammacolor s.r.l.  
Via Zeuner, 5 20822 Seveso (MB) Italy  
tel. +39 0362550550 fax +39 0362551915  
email [info@gammacolorsrl.com](mailto:info@gammacolorsrl.com)



Associazione Tessile e Salute  
Azienda associata

p.IVA 00736390964 C.F. 02639210158 c.c.i.a. Milano n. 927455 Codice ISS azienda 00736390964

## TAMPONANTE GAMMA liquido

Auxiliary with mild oxidizing action

### CHEMICAL-PHYSICAL CHARACTERISTICS:

Appearance: yellowish liquid.

Chemical constitution: derivative of benzenesulfonic acid.

pH sol. 5%: 6 ÷ 7.

Behavior in water: soluble in any ratio.

Warehouse stability: good in normal environmental conditions.

### PROPERTY:

Product is used whenever it is necessary to prevent a reducing action in both prints and dyes, especially with reactive dyes, with some dispersed dyes and in any case, with all buttock colors they have this problem.

The product is also advantageously used in the scouring of yarn-dyed articles with direct, sulfur, reactive and vat dyes, preventing the degradation of these colors by prolonged boiling, by the presence of starch or by the presence of other mild reducing agents.

### USE:

Here are some indications on the dosages that can be used:

- 1) 15 ÷ 30 gr / kg in printing paste.
- 2) 1 ÷ 3 gr / l in dyeing and purge.

Keywords: buffering, anti-reducing, anti-reduction, oxidant, protection, protective, vat, scouring, reactive dyes

The data reported are the result of accurate studies and / or experience gained, however they must be considered indicative and in any case without any guarantee on our part for use.

The data contained in this sheet are not to be considered specific.

For information: e-mail [info@gammacolorsrl.com](mailto:info@gammacolorsrl.com)